

SAFETY DATA SHEET

Issuing Date 10-Nov-2015

Revision Date 10-Nov-2015

Revision Number 3



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publicly available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name 50278MB
Mechanics Brand 45 % VOC Non CL Brake Cleaner

Recommended use of the chemical and restrictions on use

Recommended Use Brake Cleaner
Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Airosol Company, Inc.
Supplier Address P.O. Box 120
1206 Illinois St.
Neodesha
KS
66757
US

Supplier Phone Number Phone:620-325-2666

Emergency telephone number

24 Hour INFOTRAC 1-800-535-5053 (North America)
1-352-323-3500 (International)

Company Phone Number 1-800-633-9576

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

| | |
|--------------------------------------|------------|
| Acute toxicity - Oral | Category 4 |
| Acute toxicity - Dermal | Category 4 |
| Acute toxicity - Inhalation (Vapors) | Category 4 |



7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Use personal protection equipment. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Use only with adequate ventilation and in closed systems. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid contact with skin and eyes. Avoid breathing vapors or mists.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products

Strong acids. Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|----------------------------|--------------------------------------|--|---|
| Acetone 67-64-1 | STEL = 750 ppm TWA: 500 ppm | TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 1800 mg/m ³ (vacated) TWA: 750 ppm (vacated) STEL: 1000 ppm (vacated) STEL: 2400 mg/m ³ | IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m ³ |
| Methyl alcohol 67-56-1 | STEL = 250 ppm TWA: 200 ppm S* | TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S* | IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 325 mg/m ³ STEL: 250 ppm |
| Toluene 108-88-3 | TWA: 20 ppm | TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm | IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³ |
| Carbon Dioxide 124-38-9 | STEL = 30000 ppm TWA: 5000 ppm | TWA: 5000 ppm TWA: 9000 mg/m ³ (vacated) TWA: 10000 ppm (vacated) TWA: 18000 mg/m ³ (vacated) STEL: 30000 ppm (vacated) STEL: 54000 mg/m ³ | IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m ³ STEL: 30000 ppm STEL: 54000 mg/m ³ |

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992)

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves. Chemical resistant apron. Antistatic boots.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

| | | | |
|--|--------------------------|-----------------------|--------------------------|
| Physical state | Liquid spray, Aerosol | Odor | Solvent |
| Appearance | Clear, colorless | Odor Threshold | No information available |
| Color | No information available | | |
| Property | Values | Remarks | Method |
| pH | UNKNOWN | None known | |
| Melting / freezing point | No data available | None known | |
| Boiling point / boiling range | No data available | None known | |
| Flash Point | No data available | None known | |
| Evaporation Rate | No data available | None known | |
| Flammability (solid, gas) | No data available | None known | |
| Flammability Limit in Air | | | |
| Upper flammability limit | No data available | | |
| Lower flammability limit | No data available | | |
| Vapor pressure | No data available | None known | |
| Vapor density | No data available | None known | |
| Specific Gravity | 0.78 | None known | |
| Water Solubility | Insoluble | None known | |
| Solubility in other solvents | No data available | None known | |
| Partition coefficient: n-octanol/water | No data available | None known | |
| Autoignition temperature | No data available | None known | |
| Decomposition temperature | No data available | None known | |
| Kinematic viscosity | No data available | None known | |
| Dynamic viscosity | No data available | None known | |
| Explosive properties | No data available | | |
| Oxidizing properties | No data available | | |

Other Information

| | |
|----------------------------|-------------------|
| Softening Point | No data available |
| VOC Content (%) | No data available |
| Particle Size | No data available |
| Particle Size Distribution | |

10. STABILITY AND REACTIVITY**Reactivity**

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat. Heat, flames and sparks.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information**

| | |
|---------------------|---|
| Inhalation | Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Harmful by inhalation. (based on components). Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. |
| Eye contact | Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain. May cause irritation. |
| Skin contact | Specific test data for the substance or mixture is not available. Causes skin irritation. Harmful in contact with skin. (based on components). Prolonged contact may cause redness and irritation. May be absorbed through the skin in harmful amounts. Repeated exposure may cause skin dryness or cracking. |
| Ingestion | Specific test data for the substance or mixture is not available. May be fatal if swallowed and enters airways. Harmful if swallowed. (based on components). Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. |

Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---------------------------|----------------------|--------------------------|---|
| Acetone 67-64-1 | = 5800 mg/kg (Rat) | - | = 50100 mg/m ³ (Rat) 8 h |
| Methyl alcohol 67-56-1 | = 6200 mg/kg (Rat) | = 15800 mg/kg (Rabbit) | = 22500 ppm (Rat) 8 h = 64000 ppm (Rat) 4 h |
| Toluene 108-88-3 | = 2600 mg/kg (Rat) | = 12000 mg/kg (Rabbit) | = 12.5 mg/L (Rat) 4 h |



| | | | |
|--|----------------------|-------------------------|-------------------------|
| Naphtha, petroleum, hydrotreated light 64742-49-0 | > 5000 mg/kg (Rat) | > 3160 mg/kg (Rabbit) | = 73680 ppm (Rat) 4 h |
|--|----------------------|-------------------------|-------------------------|

Information on toxicological effects

Symptoms Erythema (skin redness). May cause redness and tearing of the eyes. Coughing and/ or wheezing. Difficulty in breathing. Asthma-like and/ or skin allergy-like symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects Contains a known or suspected mutagen.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen. Contains a known or suspected carcinogen.

| Chemical name | ACGIH | IARC | NTP | OSHA |
|---------------------|-------|---------|-----|------|
| Toluene 108-88-3 | | Group 3 | | |

*IARC (International Agency for Research on Cancer)
Group 3 - Not Classifiable as to Carcinogenicity in Humans*

Reproductive toxicity Contains a known or suspected reproductive toxin.

STOT - single exposure Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). If this product is a mixture, the classification is not based on toxicology studies for this product, but is based solely on toxicology studies for ingredients found within this product. Detailed substance and/or ingredient information may be provided in other sections of this SDS. Target organs effects listed in this document may result from a single overexposure to this product. Causes damage to organs if swallowed. Causes damage to organs in contact with skin.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).

Chronic Toxicity Contains a known or suspected carcinogen. Possible risk of irreversible effects. Effects from this product caused by acute exposure may cause permanent damage to target organs and/or may cause chronic conditions. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse liver effects. Contains toluene. Exposure to toluene in animals via inhalation and intentional overexposure to toluene in humans has caused adverse fetal development effects.

Target Organ Effects Respiratory system. Eyes. Skin. May affect the genetic material in germ cells (sperm and eggs). Gastrointestinal tract (GI). Reproductive System. Central Nervous System (CNS). Liver. Kidney.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
482.00 mg/kg

ATEmix (dermal)

1,521.00 mg/kg (ATE)

ATEmix (inhalation-dust/mist)

2.50 mg/l

ATEmix (inhalation-vapor)

16.00 ATEmix

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

| Chemical name | Toxicity to Algae | Toxicity to Fish | Toxicity to Microorganisms | Daphnia Magna (Water Flea) |
|--|--|--|---|---|
| Acetone 67-64-1 | | 96h LC50: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) 96h LC50: 6210 - 8120 mg/L (Pimephales promelas) 96h LC50: = 8300 mg/L (Lepomis macrochirus) | EC50 = 14500 mg/L 15 min | 48h EC50: 10294 - 17704 mg/L 48h EC50: 12600 - 12700 mg/L |
| Methyl alcohol 67-56-1 | | 96h LC50: = 28200 mg/L (Pimephales promelas) 96h LC50: > 100 mg/L (Pimephales promelas) 96h LC50: 19500 - 20700 mg/L (Oncorhynchus mykiss) 96h LC50: 18 - 20 mL/L (Oncorhynchus mykiss) 96h LC50: 13500 - 17600 mg/L (Lepomis macrochirus) | EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min | |
| Toluene 108-88-3 | 96h EC50: > 433 mg/L (Pseudokirchneriella subcapitata) 72h EC50: = 12.5 mg/L (Pseudokirchneriella subcapitata) | 96h LC50: 15.22 - 19.05 mg/L (Pimephales promelas) 96h LC50: 5.89 - 7.81 mg/L (Oncorhynchus mykiss) 96h LC50: 14.1 - 17.16 mg/L (Oncorhynchus mykiss) 96h LC50: = 5.8 mg/L (Oncorhynchus mykiss) 96h LC50: = 12.6 mg/L (Pimephales promelas) 96h LC50: 11.0 - 15.0 mg/L (Lepomis macrochirus) 96h LC50: = 54 mg/L (Oryzias latipes) 96h LC50: = 28.2 mg/L (Poecilia reticulata) 96h LC50: 50.87 - 70.34 mg/L (Poecilia reticulata) | EC50 = 19.7 mg/L 30 min | 48h EC50: 5.46 - 9.83 mg/L 48h EC50: = 11.5 mg/L |
| Naphtha, petroleum, hydrotreated light 64742-49-0 | | | | 96h LC50: = 2.6 mg/L |

Persistence and Degradability

No information available.

Bioaccumulation

| Chemical name | Log Pow |
|---------------------------|---------|
| Acetone 67-64-1 | -0.24 |
| Methyl alcohol 67-56-1 | -0.77 |
| Toluene 108-88-3 | 2.65 |

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Should not be released into the environment. Dispose of contents/containers in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number

U220 U154 U002

| Chemical name | RCRA - Halogenated Organic Compounds | RCRA - P Series Wastes | RCRA - F Series Wastes | RCRA - K Series Wastes |
|---------------------|--------------------------------------|------------------------|---|------------------------|
| Toluene 108-88-3 | | | Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution. | |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical name | California Hazardous Waste |
|---------------------------|----------------------------|
| Acetone 67-64-1 | Ignitable |
| Methyl alcohol 67-56-1 | Toxic Ignitable |
| Toluene 108-88-3 | Toxic Ignitable |

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name CONSUMER COMMODITY
Hazard Class ORM-D
Description CONSUMER COMMODITY, ORM-D

TDG

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Description UN1950, AEROSOLS, 2.1

MEX

UN-No. UN1950



Proper Shipping Name AEROSOLS
Hazard Class 2.1
Description UN1950, AEROSOLS, 2.1

ICAO

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Description UN1950, AEROSOLS, 2.1

IATA

UN-No. UN1950
Proper Shipping Name AEROSOLS, FLAMMABLE
Hazard Class 2.1
ERG Code 10L
Description UN1950, AEROSOLS, FLAMMABLE, 2.1

IMDG/IMO

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
EmS-No. F-D, S-U
Description UN1950, AEROSOLS, 2.1

RID

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Classification code 5F
Description UN1950, AEROSOLS, 2.1

ADR

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Classification code 5F
Tunnel restriction code D
Description UN1950, AEROSOLS, 2.1

ADN

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Classification code 5F
Special Provisions 190, 327, 344, 625
Description UN1950, AEROSOLS, 2.1
Hazard Labels 2.1
Limited Quantity 1 L
Ventilation VE01, VE04

15. REGULATORY INFORMATION**International Inventories**

TSCA Complies
DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical name | CAS No | Weight-% | SARA 313 - Threshold Values % |
|--------------------------|----------|----------|-------------------------------|
| Methyl alcohol - 67-56-1 | 67-56-1 | 10 - 30 | 1.0 |
| Toluene - 108-88-3 | 108-88-3 | 10 - 30 | 1.0 |

SARA 311/312 Hazard Categories

| | |
|-----------------------------------|-----|
| Acute Health Hazard | Yes |
| Chronic Health Hazard | Yes |
| Fire Hazard | Yes |
| Sudden release of pressure hazard | Yes |
| Reactive Hazard | No |

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| Toluene 108-88-3 | 1000 lb | X | X | X |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical name | Hazardous Substances RQs | Extremely Hazardous Substances RQs | RQ |
|---------------------------|--------------------------|------------------------------------|--|
| Acetone 67-64-1 | 5000 lb | | RQ= 2270 kg final RQ RQ= 5000 lb final RQ |
| Methyl alcohol 67-56-1 | 5000 lb | | RQ= 2270 kg final RQ RQ= 5000 lb final RQ |
| Toluene 108-88-3 | 1000 lb | | RQ 1000 lb final RQ RQ 454 kg final RQ |

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

| Chemical name | California Proposition 65 |
|--------------------------|---------------------------|
| Methyl alcohol - 67-56-1 | Developmental |
| Toluene - 108-88-3 | Developmental |

U.S. State Right-to-Know Regulations

| Chemical name | New Jersey | Massachusetts | Pennsylvania | Rhode Island | Illinois |
|----------------------------|------------|---------------|--------------|--------------|----------|
| Acetone 67-64-1 | X | X | X | X | |
| Methyl alcohol 67-56-1 | X | X | X | X | X |
| Toluene 108-88-3 | X | X | X | X | X |
| Carbon Dioxide 124-38-9 | X | X | X | | - |

International Regulations

Mexico**National occupational exposure limits**

| Component | Carcinogen Status | Exposure Limits |
|---------------------------------------|-------------------|--|
| Acetone 67-64-1 (45-50) | | Mexico: TWA= 1000 ppm Mexico: TWA= 2400 mg/m ³ Mexico: STEL= 1260 ppm Mexico: STEL= 3000 mg/m ³ |
| Methyl alcohol 67-56-1 (15-20) | | Mexico: TWA= 200 ppm Mexico: TWA= 260 mg/m ³ Mexico: STEL= 250 ppm Mexico: STEL= 310 mg/m ³ |
| Toluene 108-88-3 (15-20) | | Mexico: TWA 50 ppm Mexico: TWA 188 mg/m ³ |
| Carbon Dioxide 124-38-9 (5 - 10) | - | Mexico: TWA= 5000 ppm Mexico: TWA= 9000 mg/m ³ Mexico: STEL= 15000 ppm Mexico: STEL= 27000 mg/m ³ |

Mexico - Occupational Exposure Limits - Carcinogens

Canada**WHMIS Hazard Class**

Not determined

16. OTHER INFORMATION

| | | | | |
|------|--------------------|----------------|-------------------|--|
| NFPA | Health Hazards 3 | Flammability 4 | Instability 0 | Physical and Chemical Hazards - Personal Protection X |
| HMIS | Health Hazards 3 * | Flammability 4 | Physical Hazard 0 | |

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By Product Stewardship
 23 British American Blvd.
 Latham, NY 12110
 1-800-572-6501

Issuing Date 10-Nov-2015
 Revision Date 10-Nov-2015
 Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

