

74500/CI

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard.

Identity **Coltoflax****Section I**

Manufacturer's Name	Coltène/Whaledent Inc.	Emergency Tel. No.	201-512-8000
Address	750 Corporate Drive	Tel. No. for Information	201-512-8000
	Mahwah, NJ 07430	Date Prepared	1999-03
		Signature of Preparer	

Section II - Hazardous Ingredients / Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
--	----------	-----------	-----------------------------	-----------------

Section III - Physical/Chemical Characteristics

Boiling Point	> 150 °C	Specific Gravity	1.5
Vapor Pressure at °C	none (mm Hg)	Melting Point	n.k. °C
Vapor Density (AIR = 1)	n.a.	Evaporation Rate	n.a. (Butyl acetate = 1)
Solubility in Water	none		
Appearance and Odor	grey, very high viscosity silicone compound		

Section IV - Fire and Explosion Hazard Data

Flash Point	> 150 °C	Flammable Limits at °C	LEL n.a. %	UEL n.a. %
Extinguishing Media	water fog, spray, foam, halones, CO ₂ , dry extinguishing media, sand			
Special Fire Fighting Procedures	none			

Unusual Fire and Explosion Hazards none

Section V - Reactivity Data

Stability	Unstable ☐	Conditions to Avoid
	Stable ☒	none
Incompatibility (Materials to Avoid)	none	
Hazardous Decomposition or Byproducts	none	
Hazardous Polymerization	May Occur ☐	Conditions to Avoid
	Will Not Occur ☒	none