	Page: 1
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 1/30/2019
	SDS Number: R0091437
NAPA® PREMIUM CONVENTIONAL SAE 80W-85W-90 Gear Oil NP75210	Version: 1.9

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : NAPA® PREMIUM CONVENTIONAL SAE 80W-85W-90 Gear Oil

Details of the supplier of the safety data sheet

Valvoline LLC
100 Valvoline Way
Lexington, KY 40509
United States of America (USA)
1-800-TEAMVAL (1-800-832-6825)

SDS@valvoline.com

Emergency telephone number

1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number

1-800-TEAMVAL (1-800-832-6825)

Product Information

1-800-TEAMVAL (1-800-832-6825)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin sensitization : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : May cause an allergic skin reaction.

Precautionary Statements : **Prevention:**
Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves.
Response:
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/ attention.
Wash contaminated clothing before reuse.
Disposal:

SAFETY DATA SHEET

Revision Date: 09/07/2018

Print Date: 1/30/2019

SDS Number: R0091437

NAPA® PREMIUM CONVENTIONAL SAE 80W-85W-90 Gear Oil

Version: 1.9

NP75210

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	Not a hazardous substance or mixture.	>=60.00 - < 70.00
OLEFINSULFIDE	68937-96-2	Skin Sens. 1B; H317	>=1.50 - < 5.00
React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)		Flam. Liq. 4; H227 Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1; H317	>=0.50 - < 1.00

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
Wash contaminated clothing before re-use.
- In case of eye contact : Flush eyes with water as a precaution.

SAFETY DATA SHEET

Revision Date: 09/07/2018

Print Date: 1/30/2019

SDS Number: R0091437

NAPA® PREMIUM CONVENTIONAL SAE 80W-85W-90 Gear Oil

Version: 1.9

NP75210

Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.

If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
May cause an allergic skin reaction.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
Sulphur oxides

Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and : Use personal protective equipment.
Persons not wearing protective equipment should be excluded

SAFETY DATA SHEET

Revision Date: 09/07/2018

Print Date: 1/30/2019

SDS Number: R0091437

NAPA® PREMIUM CONVENTIONAL SAE 80W-85W-90 Gear Oil

Version: 1.9

NP75210

- emergency procedures : from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3	ACGIH

SAFETY DATA SHEET

Revision Date: 09/07/2018

Print Date: 1/30/2019

SDS Number: R0091437

NAPA® PREMIUM CONVENTIONAL SAE 80W-85W-90 Gear Oil

Version: 1.9

NP75210

			Inhalable fraction	
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : Respiratory protection is not required under normal conditions of use.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : amber

Odour : No data available

Odour Threshold : No data available

pH : No data available

SAFETY DATA SHEET

Revision Date: 09/07/2018

Print Date: 1/30/2019

SDS Number: R0091437

NAPA® PREMIUM CONVENTIONAL SAE 80W-85W-90 Gear Oil

Version: 1.9

NP75210

Melting point/freezing point	: No data available
Boiling point/boiling range	: > 424.9 °F / 218.3 °C (1013.333 hPa)
Flash point	: 394 - 480 °F / 201 - 249 °C Method: Cleveland open cup
Evaporation rate	: > 1 Ethyl Ether
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: < 0.1000000 mmHg
Relative vapour density	: > 1AIR=1
Relative density	: 0.89 (60.00 °F)
Density	: 0.8916 g/cm ³ (15.56 °C)
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 146 mm ² /s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.

SAFETY DATA SHEET

Revision Date: 09/07/2018

Print Date: 1/30/2019

SDS Number: R0091437

NAPA® PREMIUM CONVENTIONAL SAE 80W-85W-90 Gear Oil

Version: 1.9

NP75210

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide
Sodium oxides

SECTION 11. TOXICOLOGICAL INFORMATION
Information on likely routes of exposure

Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg


OLEFINSULFIDE:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401
Assessment: Not classified as acutely toxic by ingestion under GHS.
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: Not classified as acutely toxic by dermal absorption under GHS.
Remarks: No mortality observed at this dose.

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Acute oral toxicity : LD50 (Rat): ca. 2,000 mg/kg
Method: OECD Test Guideline 401
Assessment: The component/mixture is classified as acute

	Page: 8
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 1/30/2019
	SDS Number: R0091437
NAPA® PREMIUM CONVENTIONAL SAE 80W-85W-90 Gear Oil NP75210	Version: 1.9

oral toxicity, category 4.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation in susceptible persons.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation

Result : Slight, transient irritation

OLEFINSULFIDE:

Result : Mild skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

Remarks : Unlikely to cause eye irritation or injury.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation

Assessment : No eye irritation

OLEFINSULFIDE:

Result : Slight, transient irritation

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks : May cause allergic skin reaction.

Components:


OLEFINSULFIDE:

Test Type : Maximisation Test

Species : Guinea pig

Assessment : The product is a skin sensitiser, sub-category 1B.

Method : OECD Test Guideline 406

	Page: 9
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 1/30/2019
	SDS Number: R0091437
NAPA® PREMIUM CONVENTIONAL SAE 80W-85W-90 Gear Oil NP75210	Version: 1.9

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Test Type : Local lymph node assay
Species : Mouse
Method : OECD Test Guideline 429
Result : May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Components:

OLEFINSULFIDE:

Genotoxicity in vitro : Test Type: in vitro assay
Result: Positive results were obtained in some in vitro tests.

Genotoxicity in vivo : Test Type: Micronucleus test
Species: Mouse
Cell type: Bone marrow
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

No aspiration toxicity classification

**SAFETY DATA SHEET**

Revision Date: 09/07/2018

Print Date: 1/30/2019

SDS Number: R0091437

NAPA® PREMIUM CONVENTIONAL SAE 80W-85W-90 Gear Oil

Version: 1.9

NP75210

Further information**Product:**

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Long-term (chronic) aquatic hazard : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 hToxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l
Exposure time: 48 hToxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

OLEFINSULFIDE:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Harmful to aquatic life.

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

Revision Date: 09/07/2018

Print Date: 1/30/2019

SDS Number: R0091437

NAPA® PREMIUM CONVENTIONAL SAE 80W-85W-90 Gear Oil

Version: 1.9

NP75210

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): ca. 24 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): ca. 91.4 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 15 mg/l
End point: Growth inhibition
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 3.3 mg/l
End point: Growth inhibition
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.12 mg/l
Exposure time: 21 d
End point: Reproduction Test
Test Type: semi-static test
Test substance: WAF
Method: OECD Test Guideline 211

Ecotoxicology Assessment Short-term (acute) aquatic hazard : Toxic to aquatic life.

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

Persistence and degradability
Components:

OLEFINSULFIDE:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 13 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

SAFETY DATA SHEET

Revision Date: 09/07/2018

Print Date: 1/30/2019

SDS Number: R0091437

NAPA® PREMIUM CONVENTIONAL SAE 80W-85W-90 Gear Oil

Version: 1.9

NP75210

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 7.4 %
Exposure time: 28 d
Method: Modified Sturm Test

No data available

Bioaccumulative potential

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n-octanol/water : log Pow: Expected > 7

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Partition coefficient: n-octanol/water : Remarks: No data available

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

**SAFETY DATA SHEET**

Revision Date: 09/07/2018

Print Date: 1/30/2019

SDS Number: R0091437

Version: 1.9

NAPA® PREMIUM CONVENTIONAL SAE 80W-85W-90 Gear Oil

NP75210

SECTION 14. TRANSPORT INFORMATION**International transport regulations****REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods


INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

	Page: 14
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 1/30/2019
	SDS Number: R0091437
NAPA® PREMIUM CONVENTIONAL SAE 80W-85W-90 Gear Oil NP75210	Version: 1.9

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Respiratory or skin sensitisation

California Prop. 65

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" for carcinogenicity as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" for reproductive/developmental toxicity as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.


The components of this product are reported in the following inventories:

DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TSCA	: On TSCA Inventory

TSCA list


No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

	Page: 15
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 1/30/2019
	SDS Number: R0091437
NAPA® PREMIUM CONVENTIONAL SAE 80W-85W-90 Gear Oil NP75210	Version: 1.9

Further information

Revision Date: 09/07/2018

NFPA:	HMIS III:						
<p style="text-align: center;">Flammability</p> <div style="display: flex; align-items: center; justify-content: center;"> <div style="writing-mode: vertical-rl; transform: rotate(180deg); margin-right: 10px;">Health</div>  <div style="writing-mode: vertical-rl; margin-left: 10px;">Instability</div> </div> <p style="text-align: center;">Special hazard.</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: blue; color: white; text-align: center;">HEALTH</td><td style="text-align: center;">2</td></tr> <tr> <td style="background-color: red; color: white; text-align: center;">FLAMMABILITY</td><td style="text-align: center;">1</td></tr> <tr> <td style="background-color: yellow; text-align: center;">PHYSICAL HAZARD</td><td style="text-align: center;">0</td></tr> </table> <p style="font-size: small;">0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H227	Combustible liquid.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).


List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

	Page: 16
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 1/30/2019
	SDS Number: R0091437
NAPA® PREMIUM CONVENTIONAL SAE 80W-85W-90 Gear Oil NP75210	Version: 1.9

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System